


TEC-150 Capacity tables for collaring

Max. wall-thickness

Measures in mm



	Ø21.3	Ø26.9	Ø33.7	Ø42.4	Ø48.3	Ø60.3	Ø76.1	Ø88.9	Ø101.6	Ø114.3	Ø141.3	Ø168.3
Ø33.7	1.5	2.0	2.0	–	–	–						
Ø42.4	2.0	2.3	2.6	2.6	–	–						
Ø48.3	2.0	2.3	2.6	2.9	2.9	–						
Ø60.3	2.0	2.3	2.9	2.9	3.2	3.2						
Ø76.1	2.0	2.3	2.9	3.2	3.6	3.6	3.6	–	–	–	–	–
Ø88.9	2.0	2.3	2.9	3.2	3.6	3.6	3.6	3.9	–	–	–	–
Ø101.6	2.0	2.3	2.9	3.6	3.6	4.5	5.0	5.0	3.9	–	–	–
Ø114.3	2.0	2.3	2.9	3.6	4.0	4.5	5.0	5.6	5.0	4.5	–	–
Ø141.3	2.0	2.3	2.9	3.6	4.0	4.5	5.0	5.6	5.6	5.6	4.5	–
Ø168.3	2.0	2.3	2.9	3.6	4.0	4.5	5.0	5.6	5.6	6.3	5.6	5.0
Ø219.1	2.0	2.3	2.9	3.6	4.0	4.5	5.0	5.6	5.6	6.3	6.3	5.6
Ø273.0	2.0	2.3	2.9	3.6	4.0	4.5	5.0	5.6	5.6	6.3	6.3	6.3
Ø323.7	2.0	2.3	2.9	3.6	4.0	4.5	5.0	5.6	5.6	6.3	6.3	6.3
Ø355.6	2.0	2.3	2.9	3.6	4.0	4.5	5.0	5.6	5.6	6.3	6.3	6.3
Ø406.4	2.0	2.3	2.9	3.6	4.0	4.5	5.0	5.6	5.6	6.3	6.3	6.3

The tables are intended as a guide only. We reserve ourselves the right to alterate these values. For other wall-thicknesses and tube dimensions, please contact your T-DRILL dealer.